

PERGO® Gold™

WARRANTY

PERGO warrants that Pergo Gold underlayment will conform to the published product specifications, subject to manufacturing tolerances. Pergo (Manufacturer) warrants that Pergo Gold underlayment (“Product”) for laminate and floating wood is free from defects in manufacturing, materials and workmanship for the lifetime of the product from the original date of purchase. The warranty is nontransferable. Pergo Gold is warranted for above grade, on grade and below grade installations where the

concrete slab is within the industry tolerances. *(see note below*)*

This warranty is null and void if punctures, penetrations, rips, or torn areas are not remedied by complete coverage with aggressive tape prior to the installation. This warranty will only be effective if Pergo Gold underlayment is installed and maintained in full compliance with the product installation instructions. In addition, specific instructions, recommendations, and specifications specific to

laminate, engineered or floating wood flooring must be followed as well. Pergo is not responsible or liable for faulty installations procedures inconsistent with the flooring manufacturers’ installation instructions and maintenance procedures. Not covered is damaged caused by water and moisture accumulations caused by flood, fire, natural disaster, owner negligence or neglect, frozen or broken pipes, or similar events which result in damage or are subject to insurance coverage.



THIS EXPRESS WARRANTY IS THE SOLE WARRANTY EXTENDED AND REPLACES ANY STATUTORY WARRANTIES TO THE MAXIMUM EXTENT ALLOWABLE BY LAW.

Implied Warranties Limited in Duration and Scope

The Federal Magnuson-Moss Warranty Act limits disclaimers of implied warranties involving consumer products. To the maximum extent allowable by federal and state law, this warranty supplements or supersedes federal and state consumer goods warranty protections. There are no warranties extended beyond the description on the face hereof.

*Where concrete slabs are subject to excessive moisture, a calcium chloride test is necessary. Emissions of vapor over 5 lbs. per 1,000 square feet in a twenty four hour period requires additional protection.